

CAT5e UTP RJ45 Keystone Coupler



Applications

The Vericom VGC™ Category 5e UTP RJ45 Keystone Coupler supports 1000BASE-T (Gigabit Ethernet), 100BASE-T (Fast Ethernet), 10BASE-T (Ethernet), 155 Mb/s ATM, 622 Mb/s ATM, Digital video and broadband/baseband analog video, and Voice over Internet Protocol (VoIP).

Description / Specifications

These Vericom VGC™ Category 5e UTP RJ45 Keystone Couplers can meet ANSI/TIA-568 C Category 5e and ISO 11801 Class D channel electrical performance requirements for frequencies up to 100 MHz. These inline keystone couplers snap-in to unused keystone ports to create a pass-through connection with an RJ45 jack on both the front and rear for fast plug-in connections of patch cords to both sides. These couplers are compatible with most manufacturers' faceplates, surface mount boxes or patch panels.

To maximize system performance, combine with Vericom patch panels, patch cords, and bulk cable.


Features & Benefits

- Snap-in to unused keystone ports to create a passthrough connection for RJ45 connections.
- Excellent choice for adding a cross-connect to active electronics
- · Allows for easy extension of existing network channel
- Compatible with most manufacturers' faceplates, surface mount boxes or patch panels.
- · Available in black or white to suit your specific install.

Standards Compliance

- · RoHS Compliant
- · ISO/IEC 11801 Channel
- · ANSI TIA/EIA-568 C Channel
- IEC 61156-5

Related Products



TECHNICAL SHEETS ARE SUBJECT TO CHANGE WITHOUT NOTICE.









CAT5e UTP RJ45 Keystone Coupler

Ordering Information

Description	Black	White
CAT5e Unshielded RJ45 Keystone Coupler	MKJ5U-01349	MKJ5U-03669

Construction

Housing: Acrylonitrile butadiene styrene (ABS)

Contacts: Phosphor bronze alloy plated w/ gold over nickel plating

Mechanical


Plug Retention: 75 N (17 lbf) Wire Compatibility: 22 to 26 AWG (0.644 to 0.405 mm)


Mating Life Cycle: Min 750 cycles


Environmental Conditions


Operating Temperature: -22 °F to 140 °F (-30 °C to 60 °C) Storage Temperature: -22 °F to 140 °F (-30 °C to 60 °C)


Technical Illustration











TECHNICAL SHEETS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

REV.20250107.2