



Basic Rack Mount PDU - 15A, 120V, 1.8kW, (12) NEMA 5-15R



Description

Vericom Basic Rack Mount PDUs distribute reliable power to IT equipment in a wide variety of applications where intelligence and/or remote monitoring are not required.

This horizontal rack mount PDU features (12) NEMA 5-15R outlets (2 front-facing, 10 rear-facing) protected by a single 15A circuit breaker, a reset button in the event of an overload, and 700 joules of surge suppression. The On/Off switch includes a hinged cover to protect from accidental shutoffs and three indicator lights display the operating status. Three cord lengths are available: 3 ft (*RAPDUH3*), 6 ft (*RAPDUH1*), and 10 ft (*RAPDUH2*).

Product Features

- 12 NEMA 5-15R outlets (2 front/10 rear)
- Single 15A circuit breaker w/reset button
- 700 joules surge suppression
- Covered On/Off switch
- 3 status indicator lights

ITEM NUMBER	DESCRIPTION	CORD LENGTH
RAPDUH3	Basic rack mount PDU - 10+2 AC outlets 1U	3'
RAPDUH1	Basic rack mount PDU - 10+2 AC outlets 1U	6'
RAPDUH2	Basic rack mount PDU - 10+2 AC outlets 1U	10'


Basic Rack Mount PDU - 15A, 120V, 1.8kW, (12) NEMA 5-15R

SPECIFICATIONS	
Input Voltage	120V
Input Frequency	60Hz
Maximum Input Current	15A
Plug Type	NEMA 5-15P
Plug Style	Straight
Cord Specs	14 AWG 3-Wire Grounded SJT
Output Voltage	120V
Output Frequency	60Hz
Output Wattage	1800W
Circuit Breaker / Overload Protection	15A
Maximum Continuous Operating Voltage	130V
Outlet Quantity	2 Front / 10 Rear
Outlet Type	NEMA 5-15R
Surge Suppression	700 Joules
Protection Mode	N-H, N-G, H-G
Response Time	<1 Nanosecond
Maximum Surge Current	10KA
Maximum Surge Voltage	470V
Clamping Voltage	775V
EMI/RFI Filtration	40~60dB@10MHz
PDU Style	Rack Mount (1U)
Pre-Installed Rack Mount Brackets	Removable
Housing Material	PVC and Metal Enclosure
Product Dimensions (HxWxD)	1.75" x 17.5" (without ears)
Product Weight	3.5 lbs.
Inner Carton Quantity	1 Unit
Inner Carton Dimensions (LxWxH)	3.6" x 21.25"x 2.5"
Inner Carton Weight	3.71 lbs.
Master Carton Quantities	10 pcs.
Master Carton Dimensions (LxWxH)	13.78" x 21.65"x 11.61"
Master Carton Weight	N/W: 35 lbs. G/W: 37.1 lbs.
UL Certified Power Cord	Yes
RoHS	Yes
Operating Temperature Range	-40° to 70°
Operating Humidity	≤95%